

Knowledgebase > Lasernet FO Connector > Lasernet FO Connector FAQs > How Do I Build a Query?

How Do I Build a Query?

Alice Petruzzella - 2024-09-13 - Comments (0) - Lasernet FO Connector FAQs

Lasernet for Dynamics 365

If you wish to build a Lasernet query to extract data from Dynamics 365 Finance and Operations, it is first necessary to find out where in the system that data is. Once the location of the data is known, the query must be built in a way that enables it to reach the data. This requires knowing how tables are linked together within FO.

Sometimes, this information is already known or can be easily worked out. For example, customer information is stored in the CustTable. However, when it is not so obvious, there are ways to find out.

Find the Table and Field Names

When building a query, the first thing to do is finding the data. Here are some suggestions about how to find out the exact location of the data that your customer wants to see in their report.

Ask for Specific Requirements

The best way to make sure that the data in the query is exactly what the customer wants, is to ask them to specify the exact table and field. An example of a common request from a customer would be:

"Add the date to the Free Text Invoice report"

However, in the Free Text Invoice header, we can see that there are actually six possible dates:



What we should, instead, be asking for is a more specific requirement. The requirement should show the table name, field name and, where possible, a screenshot showing the location of the field in the user interface:

"Add CustInvoiceTable.DocumentDate field to the FreeTextInvoiceReplacement query"

×

Having a well defined requirement, the extra effort needed to work out field names and relations is avoided.

Right-Click in the User Interface

If the customer cannot provide detailed requirements, it is possible to find out wich table and field names are needed based on a screenshot that the customer provides. For example, if the customer needs to add the Invoice Text to a Free Text Invoice, the customer's requirement would read:

"Please add the Invoice text to the Invoice lines on the Free Text Invoice Replacement report, as indicated in the screenshot:"



In this case, it is easy to get the table and field information.

1. Navigate to the screen shown by the customer in the screenshot. In this case, **Accounts Receivable** > **Invoices** > **All Free Text Invoices**.



2. Find the field on the form, and right click.



3. Point to **Form Information** and, when the flyout is shown, click **Form Name:**xxxx.



The **Form Information** will be displayed, which will show the **DataSource** and **Data Field**.



Warning

The name of the **DataSource** is the value between brackets. The two values are normally the same, but can sometimes vary. Therefore, ensure that you look at the value between brackets:



Find Table Relations

The table and field names can be found by right clicking in the system to find the data, or by asking the customer to be specific, however once these tables are identified, it is necessary to know how to link them in the query.

Browser Add In Table Browser

Browser add-ins are available to access the tables in the back end of FO. This one, for example, works for Google Chrome:

https://chrome.google.com/webstore/detail/table-browser-caller-for/khhnlfooiiffofchhdhjopgpegcjlodk

It will allow you to provide a URL, an entity, and log in, in order to see the tables in an environment.



The user can then either search for a specific table, or click on **Table List** to view a list of all the different tables in the system.



This can be useful when trying to understand and build relations as it also includes a search function that makes the process of finding intermediate tables easier. Ffor instance, between logistics tables: a relation may have been built to get an email address from the LogisticsElectronicAddress table, but the Role referenced in that table is just a RecID. By searching for "Logisticselec" in the table browser, we find another table specifically for

this Role, from which we can get the label we need.



By opening the two tables, it is possible to cross reference the data and find the common features to identify how the tables are linked.

Native Table Browser

While a browser add-in is useful, some people are not able to or do not wish to install one. In this case, it is possible to use a native table browser within Finance and Operations. To do so, append the following text to the URL of your FO environment:

SysTableBrowser&tableName=<tableName>

Example

If the URL of an internal test environment were:

https://deliverytest-2-pu561bfff4965d53dee0aos.axcloud.dynamics.com/?cmp=usmf&mi=

To view the contents of the VendTable, it would be necessary to use the following URL:

https://deliverytest-2-pu561bfff4965d53dee0aos.axcloud.dynamics.com/?cmp=usmf&mi=SysTableBrowser&tablename=VendTable

Which would display the contents of the VendTable as:



This option is useful if the table name is known. However, it is not possible to search for a table as shown for the browser add-in.

Access to Visual Studio/SOL

One easy way to find the table relations is to ask a developer, or someone with access to Visual Studio or SQL. They will be able to tell you the relation between tables. This can save much work if many relations must be defined, or can be a good solution if the user already has access.

Most Used Relations

1. Customer

A. Full name

DirPartyTable.Party

Example from CustTable:

CustTable.RecId <-> DirPartyTable.RecId.

B. First name, middle name last name

DirPersonName.FirstName

DirPersonName.MiddleName

DirPersonName.LastName

From CustTable

CustTable.Party <-> DirPartyTable.RecId

DirPartyTable.RecId <->DirPerson.RecId

DirPerson.RecId <->DirPersonName.Person

C. Customer title (Mr. Mrs. Ms)

DirNameAffix.Affix

Example from CustTable

CustTable.Party <-> DirPartyTable.RecId

DirPartyTable.RecId <->DirPerson.RecId

DirPerson.PersonalTitle <-> DirNameAffix.RecId

Eksempel

Custaccount 122590

CustTable.Party=5637198169

DirPartyTable.RecId=5637198169 (It's therefore possible to jump directly from CustTable to DirPerson)

DirPerson.RecId=5637198169

DirPerson.PersonalTitle = 5637146084

DirNameAffix.RecId=5637146084

CustAccount 122590 == Ms J

D. Contact informations (Email, phone number)

DirPartyTable.PrimaryContactEmail

DirPartyTable.PrimaryContactPhone

(The ones with checkmark in primary)

Example from CustTable

CustTable Party <-> DirPartyTable RecId

DirPartyTable.PrimaryContactPhone

E. Address

LogisticsPostalAddress.Address (Address in one string)

LogisticsPostalAddress.Street

LogisticsPostalAddress.ZipCode

LogisticsPostalAddress.City

LogisticsPostalAddress.CountryRegionId

Example from CustTable

CustTable Party <-> DirPartyTable RecId

DirPartyTable_PrimaryAddressLocation <-> LogisticsPostalAddress.Location

Country name (Russia instead of RUS)

Logistics Address Country Region Translation. Short Name

LogisticsPostalAddress.CountryRegionId <->
LogisticsAddressCountryRegionTranslation.CountryRegionId

F. Delivery address

DirPartyPostalAddressView.Address (Address in one string)

(PartyLocation == 5637145327 (hardcodet for type "delivery" se knytning til type længere nede)

DirPartyPostalAddressView.City

DirPartyPostalAddressView.Street

DirPartyPostalAddressView.ZipCode

Knytning fra CustTable

CustTable.Party <-> DirPartyPostalAddressView.Party

Type (Delivery, Business etc)

LogisticsLocationRole_Type

DirPartyPostalAddresView PartyLocation <-> LogisticsLocationRole RecId

2. Translations

LanguageTxt.Txt

Example from CashDiscCode description added to the ProjectInvoice:

ProjInvoiceJour.CashDiscCode == CashDisc.CashDiscCode

CashDisc.RecId == LanguageTxt.TxtRecId

CashDisc.TableId == LanguageTxt.TableRecId

Calculated.ReportLanguage == LanguageId

Example from DIvTerm description added on a report in report language

CustTable.DlvTerm == DlvTerm.Code

DlvTerm.RecId == LanguageTxt.TxtRecId

DlvTerm.TableId == LanguageTxt.TableRecId

Calculated.ReportLanguage == LanguageId

3. Prospects

In AX common everyone starts as prospects and thereefter promoted to either customer or vendor.

Relation from prospect to customer is therefore relevant:

SmmBusRelTable.Party == CustTable.Party

(SmmBusRelTable is table for relevant prospectfields)

Bonus information

Field "BusRelTypeld" indicates if the prospect is still prospect or has been promoted to customer or vendor.

4. Contacts Title, Profession

ContactPerson.Title

ContactPerson .Profession

ContactPerson Function

Example from CustTable:

CustTable.AccountNum <-> ContactPerson.CustAccount

Bonus info:

"JobTitle" is a dropdownfield and therefor better for datadiciplin, where as "Proffesion" is a "freetextfield".

5. CompanyInfo Contact Information

CompanyInfo.invoiceAddress().Address

CompanyInfo.postalAddress().Address

CompanyInfo.email

Example from Ledger:

CompanyInfo.RecId == Ledger.PrimaryForLegalEntity

Example from SalesTable:

CompanyInfo.DataArea == SalesTable.dataAreald

Example from CustTable:

CompanyInfo.DataArea == CustTable.dataAreald

6. BankAccountTable Information

BankAccountTable.AccountNum

BankAccountTable.Name

Bank Account Table. Currency Code

BankAccountTable.SWIFTNo

BankAccountTable.IBAN

BankAccountTable.GiroContract

Example from CompanyInfo:

BankAccountTable.AccountId == CompanyInfo.Bank

BankAccountTable.dataAreald == CompanyInfo.DataArea

7. Add Bomlines to Report

There can be several active BomVersions to the InvenDimId is key to get the correct Bom.

From Quotation:

Selected tables



Data sources

←⊞

- SalesQuotationDetailsTmp
 - CustQuotationTrans
 - SalesQuotationLine
 - BOMTable

BOM

■ SalesQuotationHeaderTmp

CustQuotationJour

SysDocuBrandDetailsRegular

Add CustQuotationTrans

SalesQuotationDetailsTmp.LACTransRefRecId == CustQuotationTrans.RecId (OuterJoin 1:n)

CustQuotationTrans.InventDim == SalesQuotationLine.InventDim (OuterJoin 1:n)

CustQuotationTrans.InventTransId == SalesQuotationLine.InventTransId (OuterJoin 1:n)

(Cause BOMId is on that table)

SalesQuotationLine.ItemBOMId == BOMTable.BOMId (OuterJoin 1:n)

BOMTable.BOMId == BOM.BOMId (OuterJoin 1:n)

The BOM item number is called BOMTable.BOMId

The BOM lines Item number is called BOM. ItemId

SalesQuotation_3512_20190515_061139 -<Detail> <LACQueryRecord_DONOT_CHANGE_BOMTable>4</ LACQueryRecor</pre> <BOMId>000150</ BOMId> <RecId>68719478325</ RecId> -<BOM> <LABEL_BOM_ItemId>Item number</ LABEL_BOM_ItemId> <LABEL_BOM_RecId>Record ID</ LABEL_BOM_RecId> -<Detail_Collection> -<Detail> <LACQueryRecord_DONOT_CHANGE_BOM>5</ LACQueryReco</pre> <ItemId>M0008</ ItemId> <RecId>68719478578</ Rec d> </ Detail> <Detail> <LACQueryRecord_DONOT_CHANGE_BOM>6</ LACQueryReco</pre> <ItemId>M0009</ ItemId> <RecId>68719478579</ Rec d> </ Detail> <Detail> <LACQueryRecord_DONOT_CHANGE_BOM>7</ LACQueryReco</pre> <ItemId>M0004</ ItemId> <RecId>68719478580</ RecId> </ Detail> <Detail> <LACQueryRecord_DONOT_CHANGE_BOM>8</ LACQueryReco</p> <ItemId>M0022</ ItemId> <RecId>68719478581</ Rec d> </bedails

Add name to the bom:

BOM.ItemId == InventTable.ItemId

InventTable.Product == EcoResProductTranslation.Product

SalesQuotationTable.LanguageId == EcoResProductTranslation.languageId (SalesQuotationTable is added to SalesQuotationLine)

Selected tables

```
CustQuotationLine

SalesQuotationLine

CustQuotationLine

BOMTable

BOM
InventTable

EcoResProductTranslation
```

Name is EcoResProductTranslation.Name

```
<LACQueryRecord DONOT CHANGE BOM>15
/ LACQueryRecord DONOT CHANGE BOM>
<FIELD_BOM_RecId>68719478594</ FIELD_BOM_RecId>
<FIELD_BOM_ItemId>M0022</ FIELD_BOM_ItemId>
 <LABEL_InventTable_RecId>Record ID</ LABEL_InventTable_RecId>
-<Detail_Collection>
  -<Detail>
     <LACQueryRecord_DONOT_CHANGE_InventTable>16/ LACQueryRecord_DONOT_CHANGE_InventTable>
     <FIELD_InventTable_RecId>22565421297</ FIELD_InventTable_RecId>
    -<EcoResProductTranslation>
      <LABEL_EcoResProductTranslation_RecId>Record ID</ LABEL_EcoResProductTranslation_RecId>
       <LABEL_EcoResProductTranslation_Name>Product name</ LABEL_EcoResProductTranslation_Name>
     -<Detail_Collection>
          <LACQueryRecord_DONOT_CHANGE_EcoResProductTranslation>17
            LACQueryRecord_DONOT_CHANGE_EcoResProductTranslation>
          <FIELD_EcoResProductTranslation_RecId>22565421211</FIELD_EcoResProductTranslation_RecId>
          <FIELD_EcoResProductTranslation_Nam >>Front Grill - Metal </ FIELD_EcoResProductTranslation_Name>
        </ Detail>
      </ Detail_Collection>
     </ EcoResProductTranslation>
   </ Detail>
  </ Detail_Collection>
InventTable>
```

8. Add UnitOfmeasureConversion

Let's say you want to display the product from unit and factor on a report:

(from unit) 1 box = 4 ea (to unit)

Selected tables

□ Data sources
 □ Data sources
 □ SalesQuotationDetailsTmp
 □ CustQuotationTrans
 □ InventTable_1
 □ EcoResProduct
 □ UnitOfMeasureConversion
 UnitOfMeasure_1
 UnitOfMeasure

Add UnitOfMeasure

SalesQuotationDetailsTmp.SalesUnitTxt == UnitOfMeasure.Symbol(InnerJoin 1:1)

Add InventTable


SalesQuotationDetailsTmp.ltemId == InventTable.ltemId(InnerJoin 1:n)

EcoResProduct.RecId == InventTable.Product (InnerJoin 1:1)


UnitOfMeasureConversion.Product == EcoResProduct.RecId (InnerJoin 1:1)

UnitOfMeasure.RecId == UnitOfMeasureConversion.ToUnitOfMeasure (-||-)

Relation



UnitOfMeasure_1.RecId == UnitOfMeasureConversion.FromUnitOfMeasure Relation



Result:

```
XSL viewer - SalesQuotation 3512 20190527 124213
         <LABEL_InventTable_Product>Product</LABEL_InventTable_Product</LABEL_InventTable_RecId>Record ID</LABEL_InventTable_RecId>
            <Detail Collection>
                <LACQueryRecord_DONOT_CHANGE_InventTable_1>28</ LACQueryRecord_DONOT_CHANGE_InventTable_1>
                 <Pre><Pre><Pre><Pre><Pre><Pre>
                 <FIELD_InventTable_RecId>22565421305/ FIELD_InventTable_RecId>
                -<EcoResProduct>
                   <LABEL_EcoResProduct_RecId>Record ID</ LABEL_EcoResProduct_RecId>
                  -<Detail Collection>
                    <RecId>22565421216</ RecId>
                       <UnitOfMeasureConversion>
                         <!ABEL_UnitOfMeasureConversion_Factor>Factor

<LABEL_UnitOfMeasureConversion_Factor>

<LABEL_UnitOfMeasureConversion_FromUnitOfMeasure>From unit

<LABEL_UnitOfMeasureConversion_FromUnitOfMeasure>From unit

LABEL_UnitOfMeasureConversion_FromUnitOfMeasure>From unit
                          <LABEL UnitOfMeasureConversion Product>Product
/ LABEL UnitOfMeasureConversion Product
                          <LABEL_UnitOfMeasureConversion_RecId> Record ID 
LABEL_UnitOfMeasureConversion_RecId>
<LABEL_UnitOfMeasureConversion_ToUnitOfMeasure> To unit 
LABEL_UnitOfMeasureConversion_ToUnitOfMeasure>
                         -<Detail Collection>
                           -<Detail>
                             <LACQueryRecord_DONOT_CHANGE_UnitOfMeasureConversion>30
LACQueryRecord_DONOT_CHANGE_UnitOfMeasureConversion>
<Factor>4.00000000000

Factor>
                              <FromUnitOfMeasure>22565421247/FromUnitOfMeasure>
<Product>22565421216/Product>
<RecId>68719480077/ RecId>
                              <ToUnitOfMeasure>22565421199</ToUnitOfMeasure>
<UnitOfMeasure_1>
<LABEL_UnitOfMeasure_RecId>Record ID</LABEL_UnitOfMeasure_RecId>
                               <LABEL_UnitOfMeasure_Symbol>Unit/ LABEL_UnitOfMeasure_Symbol
-<Detail_Collection>
                                 -<Detail>
                                    <LACQueryRecord_DONOT_CHANGE_UnitOfMeasure_1>31</ LACQueryRecord_DONOT_CHANGE_UnitOfMeasure_1>
<RecId>22565421447</ RecId>
                                     <Symbol>Box</ Symbol>
                                  </ Detail>
                              </ Detail_Collection>
</ UnitOfMeasure_1>
                            </ Detail>
                          </ Detail_Collection>
                        </ UnitOfMeasureConversion>
                   </ Detail>
</ Detail_Collection>
                 </ FcoResProduct:
                 <FIELD_InventTable_ItemId>D0004/ FIELD_InventTable_ItemId>
               </ Detail>
                <LACQueryRecord_DONOT_CHANGE_InventTable_1>32</ LACQueryRecord_DONOT_CHANGE_InventTable_1>
<Product> 22565421216 </ Product>
<FIELD_InventTable_RecId> 22565421305 </ FIELD_InventTable_RecId>
                -<EcoResProduct>
<LABEL_EcoResProduct_RecId>Record ID</ LABEL_EcoResProduct_RecId>
                  -<Detail_Collection>
                       <LACQueryRecord_DONOT_CHANGE_EcoResProduct>33
LACQueryRecord_DONOT_CHANGE_EcoResProduct>
                      <RecId>22565421216</RecId>
-<UnitOfMeasureConversion>
                          <LABEL_UnitOfMeasureConversion_Factor>Factor
LABEL_UnitOfMeasureConversion_Factor>
<LABEL_UnitOfMeasureConversion_FromUnitOfMeasure>From unit
LABEL_UnitOfMeasureConversion_FromUnitOfMeasure>From unit
                          <LABEL_UnitOfMeasureConversion_Product>Product
LABEL_UnitOfMeasureConversion_Product>
<LABEL_UnitOfMeasureConversion_RecId>Record ID
LABEL_UnitOfMeasureConversion_RecId>
<LABEL_UnitOfMeasureConversion_ToUnitOfMeasure>To unit
LABEL_UnitOfMeasureConversion_ToUnitOfMeasure>
                         -<Detail_Collection>
                           -<Detail>
                              <LACQueryRecord_DONOT_CHANGE_UnitOfMeasureConversion>34
LACQueryRecord_DONOT_CHANGE_UnitOfMeasureConversion>
<Factor>10.00000000000

Factor>
                              <FromUnitOfMeasure>22565426715</FromUnitOfMeasure>
                              <Product>22565421216</ Prod
<RecId>68719480078</ RecId>
                             <ToUnitOfMeasure>22565421199</ToUnitOfMeasure>-<UnitOfMeasure_1>
                                <LABEL_UnitOfMeasure_RecId>Record ID</ LABEL_UnitOfMeasure_RecId>
                                 <LABEL_UnitOfMeasure_Symbol>Unit</ LABEL_UnitOfMeasure_Symbol</p>
                               -<Detail Collection>
                                 -<Detail>
                                   <LACQueryRecord_DONOT_CHANGE_UnitOfMeasure_1>35</ LACQueryRecord_DONOT_CHANGE_UnitOfMeasure_1>
<RecId>22565426715</ RecId>
                                   <Symbol>Bag</ Symbol>
</ Detail>
                              </ Detail_Collection>
</ UnitOfMeasure_1>
                          </ Detail>
</ Detail_Collection>
                       </ UnitOfMeasureConversion>
                   </ Detail Collection>
                 </ EcoResProduct
                 <FIELD_InventTable_ItemId>D0004</ FIELD_InventTable_ItemId>
            </ Detail>
</ Detail_Collection>

InventTable 1>


            <LABEL UnitOfMeasure RecId>Record ID</ LABEL UnitOfMeasure RecId>
             <LABEL_UnitOfMeasure_Symbol>Unit</ LABEL_UnitOfMeasure_Symbol>
            <Detail_Collection>
                 <LACQueryRecord_DONOT_CHANGE_UnitOfMeasure>2</ LACQueryRecord_DONOT_CHANGE_UnitOfMeasure>
                <FIELD_UnitOfMeasure_RecId>22565421199/ FIELD_UnitOfMeasure_RecId>
<FIELD_UnitOfMeasure_Symbol>ea/ FIELD_UnitOfMeasure_Symbol>
               </ Detail>
```

9. Add Reservation Status to your SalesLine

Add SalesLine


Add InventTransOrigin

SalesLine.InvenTransId == InventTransOrigin.InventTransId



Add InventTrans

InventTransOrigin.RecId == InventTrans.InventTransOrigin



Add fields InventTrans.StatusIssue and InventTrans.StatusReceipt for reservation status.

Result:

```
-<SalesLine>
    <LABEL_SalesLine_RecId>Record ID/ LABEL_SalesLine_RecId>
<LABEL_SalesLine_checkReservationFieldLABEL>checkReservationField():LABEL/ LABEL_SalesLine_checkReservationFieldLABEL>
    <LABEL_SalesLine_checkReservationLABEL>checkReservation():LABEL// LABEL_SalesLine_checkReservationLABEL>
<LABEL_SalesLine_Reservation>Reservation// LABEL_SalesLine_Reservation>
   -<Detail Collection>
         <LACQueryRecord_DONOT_CHANGE_SalesLine>7</ LACQueryRecord_DONOT_CHANGE_SalesLine>
         <FIELD_SalesLine_RecId>5637331333</ FIELD_SalesLine_RecId>
         FIELD_SalesLine_checkReservationFieldLABEL>false
FIELD_SalesLine_checkReservationFieldLABEL> false
FIELD_SalesLine_checkReservationLABEL>false
FIELD_SalesLine_checkReservationLABEL> false
FIELD_SalesLine_checkReservationLABEL>
         <FIELD_SalesLine_Reservation>Automatic</ FIELD_SalesLine_Reservation>
           <LABEL InventTransOrigin RecId>Record ID</LABEL InventTransOrigin RecId>
            -<Detail>
                <LACQueryRecord_DONOT_CHANGE_InventTransOrigin>8</ LACQueryRecord_DONOT_CHANGE_InventTransOrigin>
                <FIELD_InventTransOrigin_RecId>22565936042</ FIELD_InventTransOrigin_RecId>
                   <LABEL InventTrans Recid>Record ID</LABEL InventTrans Recid:
                   <LABEL_InventTrans_isWMSReserved(ABEL>isWMSReserved():LABEL</LABEL_InventTrans_isWMSReservedLABEL>
<LABEL_InventTrans_StatusIssue>Issue status/LABEL_InventTrans_StatusIssue>
                 <LABEL_InventTrans_StatusReceipt>Receipt status/ LABEL_InventTrans_StatusReceipt>
-<Detail_Collection>
                        <LACQueryRecord_DONOT_CHANGE_InventTrans>9</ LACQueryRecord_DONOT_CHANGE_InventTrans>
                      FIELD_InventTrans_RecId>22565775543</FIELD_InventTrans_RecId>
FIELD_InventTrans_RecId>
FIELD_InventTrans_RecId>
FIELD_InventTrans_isWMSReservedI_ARFI_>false</FIELD_InventTrans_isWMSReservedI_ARFI_>false</FIELD_InventTrans_StatusIssue>
FIELD_InventTrans_StatusReceipt>None</FIELD_InventTrans_StatusReceipt>
                   </ Detail_Collection>

InventTrans>
              </ Detail>

Detail Collection>
```

Example - How Do I Add Shipment Header to SalesInvoiceReplacementReport?

The SalesInvoiceReplacement report does not come with shipment data. To add it, we need to first add the following table to its data sources through the Query wizard:

WHSShipmentTable

To do so, follow these steps:

- 1. Navigate to Lasernet > Common > Reports.
- 2. In the list, find SalesInvoiceReplacement and select the desired record.
- 3. Select Query wizard.
- 4. Click **Next** until you get to Tables.



6. Use the Quick Filter to find records. In this case, find 'WHSShipmentTable'.



- 7. On the right pane, in the query data sources, select **SalesInvoiceHeaderFooterTmp**.
- 8. Click the right arrow button.



The WHSShipmentTable is added under the SalesInvoiceHeaderFooterTmp table.

9. To set the relation between these two tables, click the **Relation/Layout** button on the

top of the right pane.



- 10. On the Relation dialog, click **New**.
- 11. Set the following fields:
 - Related table: SalesInvoiceHeaderFooterTmp
 - Related field: SalesId
 - WHSShipmentTable: OrderNum
- 12. Click **OK**.



- 13. Click Next.
- 14. In the Available fields under the table 'WHSShipmentTable', select the desired fields, for example ShipmentID, LoadID, OrderNum, ProNum, shipmentManifestTrackingNumber etc. and click the right arrow to move them to the Selected fields section.



- 15. Click **Finish** and exit the Query Wizard.
- 16. Generate a Sales Invoice that has shipment info associated to it.
- 17. In Lasernet Developer, for the SalesInvoiceReplacement form, grab the XML generated from the step above and update the form design to include newly added fields.
- 18. Commit and deploy your changes.
- 19. In Dynamics 365 Finance and Operations, regenerate the Sales Invoice report.

You should be able to see the newly added fields on the report.